

omnidirectional wheels Intelligent Unmanned Forklift agv lift capacity **2T**

Basic Information

- Place of Origin:
- Brand Name: TIANYUE
- Certification: 3c.ce
- TY-ZZ-PHC-2000 Model Number:
- Minimum Order Quantity:
- wooden box • Packaging Details:
- Delivery Time: 65 wrok days
- Payment Terms:
- Supply Ability:



Product Specification

• Type:

Our Product Introduction

- Load:
- Drive:
- Size:
- Forklift Height:
- Forklift Attachments:
- Highlight:

Counterweight 1-2T

GUANGZHOU

1

T/T

100

- Mecanum Wheel Or Steering Wheel
- Customized

1700MM

- Customized
- Forklift agv 2T, 2T omnidirectional wheels forklift, omnidirectional Forklift agv

More Images



for more products please visit us on roboticsagv.com

Product Description

Intelligent Unmanned Forklift lift capacity 2T, fork lift height 1.7m, four-wheel drive, omnidirectional movement

Omnidirectional Unattended Forklift Technical Parameters

ltem	Technical Parameters
Product Name	Omnidirectional Unattended Forklift
Product Size	L3500 x W1100 x H2433 mm (customizable)
Load Mode	Front pick-up, lifting height 1700 mm
Rated Load	1500 KG - 2000 KG
Control Mode	PLC, microcontroller (customizable)
Guiding Mode	Laser, QR code, magnetic strip (as required)
Travel Direction	Forward, backward, left turn, right turn, bifurcation, 360° rotation, translation, lateral, omnidirectional
Drive Mode	McNamara wheel drive
Drive Power	DC 48V
Travel Speed	Straight: 0-40 m/min, Turning: 0-20 m/min
Repeat Positioning Accuracy	±5 mm
Permissible Road Flatness	≤5 mm
Working Mode	Continuous operation for 24 hours
Climbing Ability	≤5%
Charging Mode	Online charging (side charging)
Obstacle Sensor Safety Sensing Range	Detection distance: ≤3 m (adjustable), Sensor detection angle: ≤270° (adjustable), Emergency braking distance: < 20 mm
Safety Protection	Front obstacle detection sensor, double protection with safety touch-edge anti-collision mechanism, emergency stop switch
Alarm Form	Sound and light alarm
Work Noise	Below 70 dB (A)
Battery	Type: Lithium iron phosphate, Voltage: 48V, Capacity: 210Ah
Design Life	>10 years



Guangzhou Tianyue Automation Technology Co., Ltd.



mkliangjintian@gmail.com

C roboticsagv.com

Shop 23,24-101 ,32 Lihong Bei Lu, Jiutan Cun, Huadu District, Guangzhou City, China