



Three Way Fork Mode Automated Guided Vehicle Forklift Load 1500KG Narrow Lane

Our Product Introduction

Basic Information

- Place of Origin: GUANGZHOU
- Brand Name: TIANYUE
- Certification: 3c.ce
- Model Number: TY-BZ-SX-D1500
- Minimum Order Quantity: 1
- Packaging Details: wooden box
- Delivery Time: 65 work days
- Payment Terms: T/T
- Supply Ability: 100



Product Specification

- Drive Mode: Steering Wheel Drive
- Power Supply: Lithium Iron Phosphate
- Load Weight: 1000KG
- Forklift Type: Three-way Fork Method
- Highlight: **Three way automated guided vehicle forklift, automated guided vehicle forklift 1500KG, narrow lane automated guided forklift**



More Images



for more products please visit us on roboticsagv.com

Product Description

Intelligent Unmanned Forklift Three-way fork mode, manual/automatic mode, load 1500KG, narrow lane

Characteristic	Technical Parameters
Chassis Structure	Supports non-standard customization
Model	CDDM15J-60S
Power	Electric
Operation Method	Laser Navigation
Rated Load Capacity Q (kg)	1500
Load Center Distance C (mm)	600
Weight with Battery (kg)	6300
Wheels, Chassis	
Wheel Type	Polyurethane
Drive Wheel Specification (mm)	Φ382*142
Front Wheel Specification Ø×w (mm)	Φ145*400
Balance Wheel Specification Ø×w (mm)	Φ180*76
Wheelbase (front wheels) b10 (mm)	1305
Axle Distance y (mm)	1700
Performance Parameters	
Max Travel Speed, Unloaded/Loaded (km/h)	8/7
Ascending Speed, Unloaded/Loaded (m/s)	0.275/0.215
Descending Speed, Unloaded/Loaded (m/s)	0.150/0.195
Driving Brake	Electromagnetic Brake
Motor Parameters	
Drive Motor Power (kw)	6.5
Lift Motor Power (kw)	15
Battery Type	Lithium Battery
Battery Voltage/Capacity V/Ah	48/300
Charger V/A	48/100
Other Parameters	
Drive Control Method	AC
Data	The data is only for reference, please verify with the actual vehicles.
Dimensions	
Mast Closed Height h1 (mm)	3400
Free Lift Height h2 (mm)	2235
Lift Height h3 (mm)	6000
Max Height of Mast when Working h4 (mm)	7125
Overhead Guard Height h14 (mm)	2260/2300
Length (with fork rotated to both sides) l2(mm)	3187
Fork Ground Clearance h3 (mm)	45
Collision Guard Rail Width (mm)	1600
Fork Dimensions s/e/l (mm)	45/125/1070
Fork Adjustment Size b5 (mm)	260-650 (customizable)
Minimum Ground Clearance (axle center) m2 (mm)	32
Stacking Aisle Width Ast (mm)	1650 (1200*1200 pallet)
Aisle Guide Rail Height (mm)	120
Minimum Turning Radius Wa (mm)	2150
Main Aisle Width (mm)	3635+400
Vehicle Width b1 (mm)	1550

| Technical Parameters | 1.5 ton Three-way Stacking AGV Body |



Guangzhou Tianyue Automation Technology Co., Ltd.



13570415240



mkliangjintian@gmail.com



roboticsagv.com

Shop 23,24-101 ,32 Lihong Bei Lu, Jiutan Cun, Huadu District, Guangzhou City, China